


UI-6210RE-M-GL Rev.3



Specification

Sensor

Sensor Technology	CCD Mono
Manufacturer	Sony
Resolution (h x v)	640 x 480
Color depth (sensor)	12 bit
Color depth (camera)	12 bit
Pixel Class	VGA
Sensor Size	1/2"
Shutter	Global shutter
max. fps in Freerun Mode	122.0
Binning Modes	Mono
Subsampling Modes	-
Sensor Model	ICX414AL
Pixel size	9.9 µm
Optical Size	6.336 mm x 4.752 mm



Design

Interface	GigE
Lens Mount	C-Mount
I/O In	1 x Opto
I/O Out	1 x Opto
I/O RS-232	-
I/O GPIO	-
I/O I2C	-
Protection Class	IP65/67
Dimensions H/W/L	41.0 mm x 53.0 mm x 47.7 mm
Mass	195 g
Power supply	12V - 24V


UI-6210RE-C-HQ Rev.3



Specification

Sensor

Sensor Technology	CCD Color
Manufacturer	Sony
Resolution (h x v)	640 x 480
Color depth (sensor)	12 bit
Color depth (camera)	12 bit
Pixel Class	VGA
Sensor Size	1/2"
Shutter	Global shutter
max. fps in Freerun Mode	122.0
Binning Modes	Mono
Subsampling Modes	-
Sensor Model	ICX414AQ
Pixel size	9.9 µm
Optical Size	6.336 mm x 4.752 mm



Design

Interface	GigE
Lens Mount	C-Mount
I/O In	1 x Opto
I/O Out	1 x Opto
I/O RS-232	-
I/O GPIO	-
I/O I2C	-
Protection Class	IP65/67
Dimensions H/W/L	41.0 mm x 53.0 mm x 47.7 mm
Mass	195 g
Power supply	12V - 24V

UI-6210RE-M-GL Rev.3

