


UI-2220SE-C-HQ Rev.3



Specification

Sensor

Sensor Technology	CCD
Manufacturer	Sony
Resolution (h x v)	768 x 576
Color depth (sensor)	12 bit
Color depth (camera)	12 bit
Pixel Class	PAL
Sensor Size	1/2"
Shutter	Global shutter
max. fps in Freerun Mode	71.0
Binning Modes	Mono
Subsampling Modes	-
Sensor Model	ICX415AQ
Pixel size	8.3 μ m
Optical Size	4.781 mm x 6.374 mm



Design

Interface	USB 2
Lens Mount	C-Mount
I/O In	1 x Opto
I/O Out	1 x Opto
I/O RS-232	-
I/O GPIO	-
I/O I2C	-
Protection Class	IP30
Dimensions H/W/L	34.0 mm x 32.0 mm x 41.0 mm
Mass	79 g
Power supply	USB Cable


UI-2220SE-M-GL Rev.3



Specification

Sensor

Sensor Technology	CCD
Manufacturer	Sony
Resolution (h x v)	768 x 576
Color depth (sensor)	12 bit
Color depth (camera)	12 bit
Pixel Class	CCIR
Sensor Size	1/2"
Shutter	Global shutter
max. fps in Freerun Mode	71.0
Binning Modes	Mono
Subsampling Modes	-
Sensor Model	ICX415AL
Pixel size	8.3 μm
Optical Size	4.781 mm x 6.374 mm



Design

Interface	USB 2
Lens Mount	C-Mount
I/O In	1 x Opto
I/O Out	1 x Opto
I/O RS-232	-
I/O GPIO	-
I/O I2C	-
Protection Class	IP30
Dimensions H/W/L	34.0 mm x 32.0 mm x 41.0 mm
Mass	79 g
Power supply	USB Cable