




## Specification

### Sensor

|                                         |                                        |
|-----------------------------------------|----------------------------------------|
| Sensor type                             | CMOS Color                             |
| Shutter                                 | Rolling shutter / Global Start Shutter |
| Sensor characteristic                   | Linear                                 |
| Readout mode                            | Progressive scan                       |
| Pixel Class                             | QSXGA                                  |
| Resolution                              | 4.92 Mpix                              |
| Resolution (h x v)                      | 2560 x 1920 Pixel                      |
| Aspect ratio                            | 4:3                                    |
| ADC                                     | 12 bit                                 |
| Color depth (camera)                    | 12 bit                                 |
| Optical sensor class                    | 1/2"                                   |
| Optical Size                            | 5.632 mm x 4.224 mm                    |
| Optical sensor diagonal                 | 7.04 mm (1/2.27")                      |
| Pixel size                              | 2.2 µm                                 |
| Manufacturer                            | ON Semiconductor                       |
| Sensor Model                            | MT9P006STC                             |
| Gain (master/RGB)                       | 12.2x/5.8x                             |
| AOI horizontal                          | increased frame rate                   |
| AOI vertical                            | increased frame rate                   |
| AOI image width / step width            | 32 / 4                                 |
| AOI image height / step width           | 4 / 2                                  |
| AOI position grid (horizontal/vertical) | 4 / 2                                  |
| Binning horizontal                      | increased frame rate                   |
| Binning vertical                        | increased frame rate                   |
| Binning method                          | Color                                  |
| Binning factor                          | 2 / 3 / 4 / 6                          |
| Subsampling horizontal                  | increased frame rate                   |
| Subsampling vertical                    | increased frame rate                   |
| Subsampling method                      | Color                                  |
| Subsampling factor                      | 2, 3, 4, 5, 6                          |



## UI-5580RE-C-HQ PoE Rev.2 (AB00310)

### Model

|                                   |                    |
|-----------------------------------|--------------------|
| Pixel clock range                 | 4 MHz - 96 MHz     |
| Frame rate freerun mode           | 14                 |
| Frame rate trigger (maximum)      | 14                 |
| Exposure time (minimum - maximum) | 0.034 ms - 3404 ms |
| Power consumption                 | 2.6 W - 3.1 W      |
| Image memory                      | 64 MB              |

### Ambient conditions

The temperature values given below refer to the outer device temperature of the camera housing.


|                                     |                                 |
|-------------------------------------|---------------------------------|
| Device temperature during operation | 0 °C - 55 °C / 32 °F - 131 °F   |
| Device temperature during storage   | -20 °C - 60 °C / -4 °F - 140 °F |
| Humidity (relative, non-condensing) | 0 % - 100 %                     |

### Connectors

|                     |                                                            |
|---------------------|------------------------------------------------------------|
| Interface connector | GigE M12, screwable                                        |
| I/O connector       | 8-pin Binder connector (Binder series 712: 09-0427-020-08) |
| Power supply        | 12 V - 24 V or PoE                                         |

### Pin assignment I/O connector

|   |                                     |
|---|-------------------------------------|
| 1 | Trigger input with optocoupler (+)  |
| 2 | Input power supply (VCC) 12-24 V DC |
| 3 | General Purpose I/O (GPIO) 1        |
| 4 | Ground (GND)                        |
| 5 | Flash output with optocoupler (+)   |
| 6 | Flash output with optocoupler (-)   |
| 7 | Trigger input with optocoupler (-)  |
| 8 | General Purpose I/O (GPIO) 2        |



Camera rear view

### Design

|                  |                             |
|------------------|-----------------------------|
| Lens Mount       | C-Mount                     |
| IP code          | IP65/67                     |
| Dimensions H/W/L | 41.0 mm x 53.0 mm x 39.7 mm |
| Mass             | 175 g                       |

