



2/3" 1.4/16mm C		1/2"	1/3"
FOCAL LENGTH		f=16mm	
MAX. DIAMETER (RATIO)		F=1:1.4~16	
ELEMENT		6Gr 6 Element	
PICTURE SIZE		6.6x8.8mm	4.8x6.4 3.6x4.8
ANGLE	VER. ANGLE	22.8°	16.6° 12.4°
	HOR. ANGLE	30.5°	22.2° 16.6°
	DIA. ANGLE	38.3°	27.7° 20.8°
DISTORTION		-1.5%	-0.8% -0.4%
SHOOTING RANGE AT MINIMUM FOCUS DISTANCE	VER.	82.6mm	59.6mm 44.5mm
	HOR.	111.8mm	80.1mm 59.6mm
	DIA.	142.5mm	101.1mm 74.9mm
MINIMUM FOCUS DISTANCE		0.2m	
FLANGE BACK		17.526 mm in air	
BACK FOCUS		12.15mm in air	
FILTER SCREW SIZE		M27x0.5	
FRONT/REAR EFFECTIVE DIA.		Front Ø12.0mm Rear Ø12.8mm	
MOUNT		C-MOUNT	
EXIT PUPIL		-48.9mm	
TEMPERATURE RANGE		-10~+45° C	
STORAGE TEMPERATURE RANGE		-40~+60° C	
RESOLUTION CENTER/CORNER		Center 100LP/mm Corner 60LP/mm	

			LM16JC
			2/3" 1.4/16mm