



φ23 2.0/25mm C		
FOCAL LENGTH		f=25mm
MAX. DIAMETER (RATIO)		F=1:2.0~16
ELEMENT		6 GROUPS 8 ELEMENTS
PICTURE SIZE		13.8x18.4mm
ANGLE	VER. ANGLE	31.1°
	HOR. ANGLE	40.9°
	DIA. ANGLE	50.2°
DISTORTION (TV)		-0.57%
SHOOTING RANGE AT	VER.	93mm
	HOR.	125mm
MINIMUM FOCUS	DIA.	157mm
	MINIMUM FOCUS DISTANCE	
FLANGE BACK		17.526mm in air
BACK FOCUS		24.3mm in air
FILTER SCREW SIZE		M40.5x0.5
FRONT/REAR EFFECTIVE DIA.		FRONT φ31.4mm REAR φ18.2mm
MOUNT		C-MOUNT
EXIT PUPIL		-63.9mm
TEMPERATURE RANGE		-10~+50°C
STORAGE TEMPERATURE RANGE		-20~+60°C
RESOLUTION CENTER/CORNER		CENTER 160本/mm CORNER 80本/mm
LENS COATING		WIDE BAND MULTI COATING
WEIGHT		250 g

NOTE: Specifications and availability are subject to change without notice  
 注) 本仕様については、予告なしに変更する場合があります。



		尺度 1/1	承認 八木	製 富永 図
		機種名 φ23 F2.0 f=25mm		
		機種番 LM25XC		
2010.06.03	作成年月日			