

CCTV Lens

Model	VS-50085/M42
Focal Length	50 mm
Maximum Aperture Ratio	1:0.85
F.No	F0.85 ~ F16
Angle of view (4/3")	15.7° × 20.9° (Diagonal: 25.9°)
M.O.D	240 mm
Flange back	19.53 mm
Operation of Iris & Focus	Manual
Mount	M 42 P= 1.0
Filter Thread	M 62 P= 0.75
TV distortion (4/3")	-0.3 %
Sensor size (max.)	4/3"
Weight (approx.)	620 g
Dimension	φ 65 (MAX) × L= 79.5 mm

※Maximum Aperture Ratio is 1:0.90 with C-mount customized

△				APPROVED	CHECKED	<u>MATERIAL</u> 材料				—		<u>CHAMFER</u> 一般面取		—		<u>QUANTITY</u> 個数
△				T. A.	T. A.	<u>TREATMENT</u> 処理				—		<u>FINISHING</u> 仕上		—		—
△						<u>TREATMENT CONTACT</u> 処理接点				—		<u>DECENTRATION</u> 偏芯		—		
△						OVER 250 UP TO 1000	±0.3	±0.5	±1.0	±0.2	UNIT (mm)	ANGLE 角度	<u>METHOD</u> 図法	<u>REMARK</u> 適用（機種名）		
△				DESIGNED	DRAWN	OVER 63 UP TO 250	±0.2	±0.3	±0.6	±0.15		—		V S - 5 0 0 8 5 / M 4 2		
△				T. A.	T. T.	OVER 16 UP TO 63	±0.1	±0.2	±0.4	±0.1	SCALE	1 / 1	NAME	外 観 図		
△						OVER 0 UP TO 16	±0.05	±0.1	±0.2	±0.1				DATE	' 12. 11. 21	DRAW NO.
	DATE	EXCH NO.	REVISION 変更記事			<u>TOLERANCES</u>				A	B	C	S			